



The information and content in this document is provided for informational purposes only and is provided "as is" with no warranties of any kind, either express or implied, including without limitation any warranties of merchantability, fitness for a particular purpose, and non-infringement. GFI Software disclaims and in no event shall be liable for any losses or damages of any kind, including any consequential or incidental damages in connection with the furnishing, performance or use of this document. The information is obtained from publicly available sources. Though reasonable effort has been made to ensure the accuracy of the data provided, GFI makes no warranty, promise or guarantee about the completeness, accuracy, recency or adequacy of information contained in this document and is not responsible for misprints, out-of-date information, or errors. GFI reserves the right to revise or update its products, software or documentation without notice. You must take full responsibility for your use and application of any GFI product or service. No part of this documentation may be reproduced in any form by any means without prior written authorization of GFI Software.

If you believe there are any factual errors in this document, please contact us and we will review your concerns as soon as practical.

GFI and Kerio Control are trademarks or registered trademarks of GFI Software or its affiliates in the US and other countries. Any other trademarks contained herein are the property of their respective owners.

Kerio Control is copyright of Kerio. - 1999-2020 Kerio. All rights reserved.

Document Version: 9.2.8

Last updated (month/day/year): 06/30/2021

1 Introduction

Kerio Control provides a combination of Unified Threat Management and Next-Generation firewall which helps you to protect, manage and monitor your network and users' behavior.

Kerio Control, as a Unified Threat Management solution, preserves the integrity of your servers with deep packet inspection and advanced network routing capabilities, including simultaneous IPv4 and IPv6 support. You can create inbound and outbound traffic policies, restrict communication by specific URL, application, traffic type, content category and time of day.

IPS adds a transparent layer of network protection, with Snort-based behavior analysis, and a regularly updated database of rules and blacklisted IP addresses from Emerging Threats.

The optional anti-virus service scans all web and FTP traffic, email attachments and downloads, automatically updating itself with the latest virus definitions. Kerio Antivirus allows you to keep viruses, worms, trojans and spyware from infesting your network.

The optional Kerio Control Web Filter with application awareness limits legal liability, protects your network and boosts user productivity by limiting user access to dangerous or inappropriate sites or those that just plain waste time.

You can easily prioritize and monitor network traffic to guarantee high-speed transmission for the most important traffic types. Internet Link Load Balancing optimizes Internet access by distributing traffic across multiple links. Kerio Control monitors link availability.

Kerio Control QoS gives you control over how much bandwidth each type of network traffic can consume.

You can get detailed usage reporting with Kerio Control Statistics. This component lets managers and admins view the Internet and application activities of individual users.

With Kerio Control VPN or industry-standard IPsec/L2TP, you can link headquarters to remote users and branch offices.

The Kerio Control web based administration is clean and simple, and you can upgrade to the latest version automatically or manually with just one click.

Kerio Control supports flexible deployment. You can opt for a software appliance, a virtual machine, or a performance-optimized hardware appliance. Remote deployment of hardware appliances is easier and faster than ever before with self-provisioning through https://go.gfi.com/?pageid=ControlMyKerio.


www.gfi.com 1 Introduction | 3

2 NG Hardware Series

NG110 NG310 NG510 and NG511







2.0.1 Hardware Models (Only available in US, Canada, APAC and EU)

Kerio Control Appliances	NG110	NG310	NG510 and NG511
Max Users	20	80	300
Suggested Users	10	50	200
Software	Kerio Control with Kerio Antivirus and Kerio Web Filter		

2.0.2 Data Sheet Specifications

	NG110	NG310	NG510	NG511	
Processor	Intel® Celeron® Pro- cessor N3010	Intel Atom® Processor C3558	Intel® Core™ i5-7500 Processor	Intel® Core™ i5-7500 Processor	
Ethernet Ports	3 x GbE RJ45	6 x GbE RJ45, 2 x SFP	6 x GbE RJ45	14 x GbE RJ45	
RAM	8GB DDR3 Memory	8GB DDR4 Memory	16GB DDR4 Memory	16GB DDR4 Memory	
Memory	32GB mSATA	32GB, 2.5" SATA SSD	32GB, 2.5" SATA SSD	32GB, 2.5" SATA SSD	
I/O Interfaces	1 x RJ45 Console, 1 x USB 3.0, 1 x USB 2.0, 1 x HDMI port	1x RJ45 Console, 2 x USB 2.0	1 x RJ45 Console, 2 x USB 2.0, LCD Display	1 x RJ45 Console, 2 x USB 2.0, LCD Display	
Cooling	No Fan	1 x Cooling Fan w/ Smart Fan	2 x Cooling Fans	2 x Cooling Fans	
Firewall Throughput	500 Mbps	900 Mbps	900 Mbps	900 Mbps	
Weight (lb/kg)	1,1 lb / 0.5 kg	2.6 lb / 1.2 kg	16.5 lb / 7.5 kg	16.5 lb / 7.5 kg	
Dimensions	(W x H x D) 136.76 mm x 35.5 mm x 119.66 mm (5.38" x 1.40" x 4.71")	(W x H x D) 231 mm x 44 mm x 200 mm (9.09" x 1.73" x 7.87")	(W x H x D) 438 mm x 44 mm x 321 mm (17.24" x 1.73" x 12.64")	(W x H x D) 438 mm x 44 mm x 321 mm (17.24" x 1.73" x 12.64")	
Chassis	Fanless design	Desktop design	1U Rack mount unit	1U Rack mount unit	
UTM Throughput	300 Mbps	700 Mbps	900 Mbps	900 Mbps	
Power input	36W	60W	220W	220W	
Warranty	Standard 1 year warranty, upgradable to 3 years				

www.gfi.com 2 NG Hardware Series | 4